

6"

6SP60

Vinco®

6"

6SP60

Vinco®

SIZE CHARTS

Model	A	B	C	D	E	Φmax
6SP60-11	2533	1017	1516	G3"/G4"	144	145
6SP60-12	2646	1017	1629			
6SP60-13	2804	1062	1742			
6SP60-14	2917	1062	1855			
6SP60-15	3030	1062	1968			
6SP60-16	3198	1117	2081			
6SP60-17	3401	1207	2194			
6SP60-18	3514	1207	2307			
6SP60-19	3627	1207	2420			
6SP60-20	3740	1207	2533			
6SP60-21	3853	1207	2646			
6SP60-22	3864	1105	2759			
6SP60-24	3977	1105	2872			
6SP60-26	4398	1413	2985			
6SP60-28	4511	1413	3098			
6SP60-30	4624	1413	3211			



SELECTION CHARTS

Model 50Hz	Motor Power		Three Phase 380V	Q US.gpm m³/h l/min	Capacity							
					0	106	158	185	211	238	264	290
					0	24	36	42	48	54	60	66
	HP	kW	A	H m	Total head in meters							
					0	106	158	185	211	238	264	290
					0	24	36	42	48	54	60	66
6SP60-11	30	22	46	H m	156	138	125	116	106	95	83	69
6SP60-12	30	22	46		170	151	136	127	116	104	90	75
6SP60-13	35	26	54		184	164	147	137	126	113	98	81
6SP60-14	35	26	54		198	176	159	148	135	121	105	88
6SP60-15	35	26	54		212	189	170	158	145	130	113	94
6SP60-16	40	30	62		227	201	181	169	155	139	121	100
6SP60-17	50	37	74		241	214	193	180	164	147	128	106
6SP60-18	50	37	74		255	226	204	190	174	156	136	113
6SP60-19	50	37	74		269	239	215	201	184	165	143	119
6SP60-20	50	37	74		283	252	227	211	194	173	151	125
6SP60-21	50	37	74		297	264	238	222	203	182	158	131
6SP60-22	60	45	86		311	277	249	232	213	191	166	138
6SP60-24	60	45	86		340	302	272	253	232	208	181	150
6SP60-26	75	55	117		368	327	295	275	252	225	196	163
6SP60-28	75	55	117		396	352	317	296	271	243	211	175
6SP60-30	75	55	117		425	377	340	317	290	260	226	188

