

6"

R150-BS

Vinco®

6"

R150-BS

Vinco®

Electric submersible pump R150 series is suitable for lifting clean water in wells, domestic, civil and industrial applications, including water supply, irrigation systems. R150-BS series capacity range: 6m³/h ~ 18m³/h, max total head: 384m.

Suction support and delivery door in Stainless steel



SIZE CHARTS

Model	A	B	C	D	E	Φmax
R150-BS-02	926	441	485	G2 1/2"	95	150
R150-BS-03	1025	501	524			
R150-BS-04	1123	561	562			
R150-BS-06	1241	601	640			
R150-BS-08	1322	607	715			
R150-BS-11	1475	642	833			
R150-BS-14	1628	682	946			
R150-BS-16	1792	717	1075			
R150-BS-19	1938	747	1191			
R150-BS-21	2062	794	1268			
R150-BS-23	2171	824	1347		135	



SELECTION CHARTS

Items marked with * are equipped with 4" motor

Model 50Hz	Motor Power		Three Phase	Q	Capacity							
				US.gpm	0	26	35	44	53	62	70	79
				m³/h	0	6	8	10	12	14	16	18
	380V	l/min	0	100	133	167	200	233	267	300		
	HP	kW	A	Total head in meters								
R150-BS-02*	2	1.5	4.4	H m	33	31	30	27	25	21	16	9
R150-BS-03*	3	2.2	6.2		50	45	44	41	38	31	24	10
R150-BS-04	4	3	8.3		66	61	59	56	51	43	36	20
R150-BS-06	5.5	4	10.3		99	92	89	84	76	65	50	32
R150-BS-08	7.5	5.5	14		132	122	116	110	102	88	68	42
R150-BS-11	10	7.5	18.5		183	171	164	155	140	122	100	68
R150-BS-14	12.5	9.2	21		232	217	200	194	170	151	120	80
R150-BS-16	15	11	24		264	247	230	224	200	177	140	98
R150-BS-19	17.5	13	28		324	296	283	265	243	210	169	116
R150-BS-21	20	15	32		348	328	313	290	268	236	190	120
R150-BS-23	25	18.5	40		384	359	343	321	293	250	200	130

