

6"

R150-GS

Vinco®

6"

R150-GS

Vinco®

Electric submersible pump R150 series is suitable for lifting clean water in wells, domestic, civil and industrial applications, including water supply, irrigation systems. R150-GS series capacity range: 12m³/h ~ 48m³/h, max total head: 254m.

Suction support and delivery door in Stainless steel



SIZE CHARTS

Model	A	B	C	D	E	ΦMax
R150-GS-02	1165	561	604	G3"	135	150
R150-GS-03	1295	601	694			
R150-GS-04	1393	607	786			
R150-GS-05	1522	642	880			
R150-GS-06	1697	682	1015			
R150-GS-07	1822	717	1105			
R150-GS-08	1944	747	1197			
R150-GS-09	2080	794	1286			
R150-GS-11	2292	824	1468			
R150-GS-14	2653	864	1789			
R150-GS-16	2889	921	1968			
R150-GS-18	3130	981	2149			



SELECTION CHARTS

Model 50Hz	Motor Power		Three Phase	Q	Capacity							
				US.gpm	0	53	79	106	132	159	185	211
				m³/h	0	12	18	24	30	36	42	48
			380V	l/min	0	200	300	400	500	600	700	800
	HP	kW	A	Total head in meters								
R150-GS-02	4	3	8.3	H m	28	26	25	24	23	21	19	16
R150-GS-03	5.5	4	10.3		42	39	37	36	34	31	28	24
R150-GS-04	7.5	5.5	14		57	52	50	48	45	42	37	31
R150-GS-05	10	7.5	18.5		71	65	62	60	57	52	47	39
R150-GS-06	12.5	9.2	21		85	78	75	72	68	63	56	47
R150-GS-07	15	11	24		99	91	87	84	79	73	65	55
R150-GS-08	17.5	13	28		113	104	100	96	91	84	75	63
R150-GS-09	20	15	32		127	117	112	108	102	94	84	71
R150-GS-11	25	18.5	40		155	143	137	132	125	115	103	86
R150-GS-14	30	22	46		198	182	175	168	159	147	131	110
R150-GS-16	35	26	54		226	208	200	192	181	168	150	126
R150-GS-18	40	30	62		254	234	225	215	204	189	168	141

